



# DISHWASHER UX-50B 400/50/3N

Rack size 500x500mm and door clearance 380 mm. Multi-power version.



P/N 1303224



WARE WASHING  
COMMERCIAL DISHWASHERS

## SALES DESCRIPTION

- ✓ Sani-Control: guaranteed disinfection
- ✓ Embedded bodywork and easy-grip door: hygienic and ergonomic
- ✓ Exclusive Hydroblade™ washing arms: maximum effectiveness.
- ✓ 3-stage filtering system.
- ✓ Double-walled body (partial).

### Sani-Control guarantee

- ✓ GUARANTEED DISINFECTION in compliance with standard DIN 10534.
- ✓ THERMAL LOCK function: Ensures that rinsing will be carried out at the ideal temperature to disinfect the dishes.

### New recessed bodywork

- ✓ Ergonomic design with rounded corners to prevent the accumulation of dirt and facilitate cleaning.
- ✓ Compact tank volume (50% water saving compared to the previous range).
- ✓ Embedded basket guides

### Hydroblade™ washing arms

- ✓ Redesigned nozzles for greater washing performance.
- ✓ The “monoblock” design delivers durability and resistance to impacts.
- ✓ 30% savings in water consumption during rinsing compared to the previous range.

### 3-stage filter system: surface, tank and extraction

- ✓ Keeps the washing water in optimal conditions to maintain constant washing performance.
- ✓ The surface filters feature an “easy-on” design and can be quickly removed without having to disconnect the washing arms.

### “Easy grip” door: new design with integrated door handle

- ✓ The integration of the components provides greater resistance and robustness.
- ✓ Designed to have no corners or areas that are difficult to access: prevents deposits of dirt and facilitates cleaning.
- ✓ Its ergonomic handle provides a perfect grip, even with wet hands.
- ✓ Double-walled door with safety microswitch and high quality seal
- ✓ 38 cm loading capacity: high versatility for washing a wide range of items: dishes, Euronorm trays, GN 1/1 tubs and pizza plates diam 39

### Premium warewashing

- ✓ Ultra Xperience: high performance, without complications.
- ✓ Soft start: progressive start-up of the washing pump to protect fragile items.
- ✓ Colour LCD Display: intuitive communication of the machine status by means of messages, colour codes and icons.
- ✓ Dedicated cycles: selection of the ideal washing programme using icons.
- ✓ Adaptable: allows the main parameters of the machine to be adjusted to the needs of each user.
- ✓ TEMPERATURE DISPLAY
- ✓ Wash Plus+ function: increases the intensity of the wash cycle for greater cleaning performance
- ✓ Control panel with IP65 humidity protection.

### You will never WASH ALONE

- ✓ Tech-Services: our team of technicians will help you so that your machine is always ready for use.
- ✓ Design Services: tell us what your needs are and we will advise you.
- ✓ 60 years of experience and know-how at your disposal.

## INCLUDES

- ✓ Drainage pump with level sensor. Proactive tank water renewal.
- ✓ Rinse aid pump.
- ✓ 1 glasses basket.
- ✓ 1 mixed basket (plates).
- ✓ 1 small basket for cutlery.

## OPTIONAL

- Detergent dosing kit.
- Double-level accessory for washing two baskets at the same time.

## ACCESSORIES

- Manual water softeners
- Automatic water softeners
- 500 x 500 mm. baskets
- Inserts & supplements
- High Feet Kit
- Reverse Osmosis device OS-140P
- Dosing equipments front AX / UX glass- and undercounter dishwashers

## SPECIFICATIONS

Basket dimensions: 500 mm x 500 mm

Maximum glass height: 380 mm

Cycle duration: 90/110/120/180/240 “

Production baskets/hour: 40/33/30/20/15

Wash temperature: 40 °C - 65 °C

Rinse temperature: 65 °C - 87 °C

Boiler capacity: 8 l

Wash tank capacity: 15 l

### Consumption and savings

Water consumption/cycle: 2.5 l

Automatic saving mode in: 25 ‘

Automatic switch-off: 120 ‘





# DISHWASHER UX-50B 400/50/3N

Rack size 500x500mm and door clearance 380 mm. Multi-power version.



P/N 1303224

### Loading

Pump: 750 W / 1 Hp  
Tank: 1800 W  
Boiler: 5000 W  
Total loading: 5750 W

**Electrical supply:** 400 V / 50 Hz / 3N ~ (8.5 A)  
Electrical connection: --

### Electrical supply - multi-phase options

- ✓ 400 V / 50 Hz / 3N ~ (Default)
- ✓ 230 V / 50 Hz / 1 ~
- ✓ --


### External dimensions (WxDxH)

- ✓ Width: 580 mm
- ✓ Depth: 635 mm
- ✓ Height: 835 mm

Net weight: 58 Kg  
Noise level (1m.): <69 dB(A)

### Crated dimensions

640 x 695 x 960 mm  
Gross weight: 65 Kg



WARE WASHING  
COMMERCIAL DISHWASHERS

**sammic** | www.sammic.com  
Food Service Equipment Manufacturer

Polígono Basarte, 1. phone +34 943 15 72 36  
20720 Azkoitia, Spain sales@sammic.com



Project	Date
Item	Qty
Approved	

product sheet  
updated 20/07/2022